

WHAT IS CLAIMED IS:

1. Apparatus for determining one or more parameters of an electrochemical cell or battery comprising:
response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of time-varying electrical excitation of said cell or battery; and,
computation circuitry coupled to said response sensing circuitry and adapted to utilize said response to evaluate elements of a circuit model comprising the series combination of a series R-L subcircuit and a plurality of parallel G-C subcircuits, said computation circuitry further adapted to evaluate one or more said parameters from values of one or more said elements.
2. The apparatus of claim 1 wherein said time-varying electrical excitation comprises current excitation and said time-varying electrical response comprises voltage response.

10073378-020003

14. The apparatus of claim 1 wherein one said parameter is state-of-charge.
15. The apparatus of claim 14 wherein said computation circuitry computes said state-of-charge from the value of the conductance element of a particular parallel G-C subcircuit and the value of the capacitance element of a different parallel G-C subcircuit of said electrical circuit representation.
16. The apparatus of claim 1 wherein one said parameter is total storage capacity.
17. The apparatus of claim 16 wherein said computation circuitry computes said total storage capacity from the value of the conductance element of a particular parallel G-C subcircuit and the value of the capacitance element of a different parallel G-C subcircuit of said electrical circuit representation.
18. The apparatus of claim 1 wherein one said parameter is maximum exchange current.
19. The apparatus of claim 18 wherein said computation circuitry computes said maximum exchange current from the value of the

20250307 09:00:00

conductance element of a particular parallel G-C subcircuit and the value of the capacitance element of a different parallel G-C subcircuit of said electrical circuit representation.

20. The apparatus of claim 1 wherein one said parameter is charge transfer conductance.
21. The apparatus of claim 20 wherein said computation circuitry computes said charge transfer conductance from the value of the conductance element of a particular parallel G-C subcircuit of said electrical circuit representation.
22. The apparatus of claim 1 wherein one said parameter is double layer capacitance.
23. The apparatus of claim 22 wherein said computation circuitry computes said double layer capacitance from the value of the capacitance element of a particular parallel G-C subcircuit of said electrical circuit representation.
24. The apparatus of claim 1 wherein one said parameter is maximum charge transfer conductance.

25. The apparatus of claim 24 wherein said computation circuitry computes said maximum charge transfer conductance from the value of the conductance element of a particular parallel G-C subcircuit and the value of the capacitance element of a different parallel G-C subcircuit of said electrical circuit representation.
26. The apparatus of claim 1 wherein one said parameter is maximum double layer capacitance.
27. The apparatus of claim 26 wherein said computation circuitry computes said maximum double layer capacitance from the value of the conductance element of a particular parallel G-C subcircuit and the value of the capacitance element of a different parallel G-C subcircuit of said electrical circuit representation.
28. The apparatus of claim 1 wherein one said parameter is absolute cranking current.
29. The apparatus of claim 28 wherein said computation circuitry computes said absolute cranking current from the value of the resistance element of said series R-L subcircuit.

10073376-020804

30. The apparatus of claim 1 wherein one said parameter is fully charged cranking current.
31. The apparatus of claim 30 wherein said computation circuitry computes said fully charged cranking current from the value of the conductance element of a particular parallel G-C subcircuit, the value of the capacitance element of a different parallel G-C subcircuit, and the value of the resistance element of said series R-L subcircuit of said electrical circuit representation.
32. The apparatus of claim 31 wherein one said parameter is state-of-health.
33. The apparatus of claim 32 including an input device coupled to said computation circuitry wherein said computation circuitry computes state-of-health by comparing said fully charged cranking current with a reference number determined in accordance with a battery rating inputted on said input device.
34. The apparatus of claim 33 wherein said battery rating comprises a cold cranking ampere battery rating.

10073376-020002

series R-L subcircuit and a plurality of parallel G-C subcircuits; and, determining values of one or more said parameters from values of one or more said elements.

40. The method of claim 39 wherein said time-varying electrical excitation comprises current excitation and said time-varying electrical response comprises voltage response.
41. The method of claim 39 wherein said time-varying electrical excitation comprises voltage excitation and said time-varying electrical response comprises current response.
42. The method of claim 40 including applying said time-varying electrical excitation to said cell or battery with an external source.
43. The method of claim 42 wherein said external source comprises a cell/battery charger or an alternator employed to charge said electrochemical cell or battery.
44. The method of claim 39 including displaying one or more said parameters to a user.

2025 RELEASE UNDER E.O. 14176

45. The method of claim 39 including controlling a process device in accordance with the value or values of one or more said parameters.
46. The method of claim 45 wherein said process device is a cell/battery charger charging said electrochemical cell or battery.
47. The method of claim 39 including actuating an alarm in accordance with values of one or more said parameters.
48. The method of claim 39 wherein one said parameter is absolute stored charge.
49. The method of claim 48 including determining said absolute stored charge from the value of the capacitance element of a particular parallel G-C subcircuit of said electrical circuit representation.
50. The method of claim 39 wherein one said parameter is exchange current.
51. The method of claim 50 including determining said exchange current from the value of the conductance element of a particular parallel G-C subcircuit of said electrical circuit representation.

20250307 09:00:00

52. The method of claim 39 wherein one said parameter is state-of-charge.
53. The method of claim 52 including determining said state-of-charge from the value of the conductance element of a particular parallel G-C subcircuit and the value of the capacitance element of a different parallel G-C subcircuit of said electrical circuit representation.
54. The method of claim 39 wherein one said parameter is total storage capacity.
55. The method of claim 54 including determining said total storage capacity from the value of the conductance element of a particular parallel G-C subcircuit and the value of the capacitance element of a different parallel G-C subcircuit of said electrical circuit representation.
56. The method of claim 39 wherein one said parameter is maximum exchange current.
57. The method of claim 56 including determining said maximum exchange current from the value of the conductance element of a particular parallel G-C subcircuit and the value of the capacitance element of a different parallel

10073378-020202

G-C subcircuit of said electrical circuit representation.

58. The method of claim 39 wherein one said parameter is charge transfer conductance.
59. The method of claim 58 including determining said charge transfer conductance from the value of the conductance element of a particular parallel G-C subcircuit of said electrical circuit representation.
60. The method of claim 39 wherein one said parameter is double layer capacitance.
61. The method of claim 60 including determining said double layer capacitance from the value of the capacitance element of a particular parallel G-C subcircuit of said electrical circuit representation.
62. The method of claim 39 wherein one said parameter is maximum charge transfer conductance.
63. The method of claim 62 including determining said maximum charge transfer conductance from the value of the conductance element of a particular parallel G-C subcircuit and the value of the capacitance element of a

10073370-000000

different parallel G-C subcircuit of said electrical circuit representation.

64. The method of claim 39 wherein one said parameter is maximum double layer capacitance.
65. The method of claim 64 including determining said maximum double layer capacitance from the value of the conductance element of a particular parallel G-C subcircuit and the value of the capacitance element of a different parallel G-C subcircuit of said electrical circuit representation.
66. The method of claim 39 wherein one said parameter is absolute cranking current.
67. The method of claim 66 including determining said absolute cranking current from the value of the resistance element of said series R-L subcircuit.
68. The method of claim 39 wherein one said parameter is fully charged cranking current.
69. The method of claim 68 including determining said fully charged cranking current from the value of the conductance element of a particular parallel G-C subcircuit, the value

of the capacitance element of a different parallel G-C subcircuit, and the value of the resistance element of said series R-L subcircuit of said electrical circuit representation.

70. The method of claim 39 wherein one said parameter is state-of-health.
71. The method of claim 70 including inputting a battery rating with an input device and determining said state-of-health by comparing said fully charged cranking current with a reference number determined in accordance with said battery rating.
72. The method of claim 71 wherein said battery rating comprises a cold cranking ampere battery rating.
73. The method of claim 55 wherein one said parameter is state-of-health.
74. The method of claim 73 including inputting a battery rating with an input device and determining said state-of-health by comparing said total storage capacity with a reference number determined in accordance with said battery rating.

10073376-00000

75. The method of claim 74 wherein said battery rating comprises an ampere-hour battery rating.
76. The method of claim 74 wherein said battery rating comprises a reserve capacity battery rating.
77. Apparatus for determining one or more parameters of an electrochemical cell or battery adapted to perform the method according to claim 39.
78. Apparatus for determining absolute stored charge of an electrochemical cell or battery comprising:
response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of time-varying electrical excitation of said cell or battery; and,
computation circuitry coupled to said response sensing circuitry and adapted to utilize said response to evaluate elements of a circuit model containing a plurality of parallel G-C subcircuits connected in series, said computation circuitry further adapted to evaluate said absolute stored charge from the

10073378-000000

value of the capacitance element of a particular parallel G-C subcircuit.

79. Apparatus for determining an exchange current of an electrochemical cell or battery comprising:

response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of time-varying electrical excitation of said cell or battery; and,

computation circuitry coupled to said response sensing circuitry and adapted to utilize said response to evaluate elements of a circuit model containing a plurality of parallel G-C subcircuits connected in series, said computation circuitry further adapted to evaluate said exchange current from the value of the conductance element of a particular parallel G-C subcircuit.

80. Apparatus for determining state-of-charge of an electrochemical cell or battery comprising:

response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of

time-varying electrical excitation of said cell or battery; and, computation circuitry coupled to said response sensing circuitry and adapted to utilize said response to evaluate elements of a circuit model containing a plurality of parallel G-C subcircuits connected in series, said computation circuitry further adapted to evaluate said state-of-charge from the value of the conductance element of a particular parallel G-C subcircuit and the value of the capacitance element of a different parallel G-C subcircuit.

81. Apparatus for determining total storage capacity of an electrochemical cell or battery comprising:

response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of time-varying electrical excitation of said cell or battery; and,

computation circuitry coupled to said response sensing circuitry and adapted to utilize said response to evaluate elements of a circuit model containing a plurality of parallel G-C subcircuits connected in series, said computation

20250903 09:47:00

82. Apparatus for determining maximum exchange current of an electrochemical cell or battery comprising:

response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of time-varying electrical excitation of said cell or battery; and,

computation circuitry coupled to said response sensing circuitry and adapted to utilize said response to evaluate elements of a circuit model containing a plurality of parallel G-C subcircuits connected in series, said computation circuitry further adapted to evaluate said maximum exchange current from the value of the conductance element of a particular parallel G-C subcircuit and the value of the capacitance element of a different parallel G-C subcircuit.

83. Apparatus for determining absolute cranking current of an electrochemical cell or battery comprising:
- response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of time-varying electrical excitation of said cell or battery; and,
- computation circuitry coupled to said response sensing circuitry and adapted to utilize said response to evaluate elements of a circuit model containing a series R-L subcircuit in series with a plurality of parallel G-C subcircuits, said computation circuitry further adapted to evaluate said absolute cranking current from the value of the resistance element of said series R-L subcircuit.
84. The apparatus of claim 83 wherein said computation circuitry computes fully charged cranking current by correcting said absolute cranking current with a correction factor evaluated using values of a capacitance element contained in a particular parallel G-C subcircuit and a conductance element contained in a different parallel G-C subcircuit of said circuit model.

10073276-000002

85. The apparatus of claim 84 including an input device wherein said computation circuitry computes state-of-health by comparing said fully charged cranking current with a reference number in accordance with a battery rating inputted on said input device.
86. The apparatus of claim 85 wherein said battery rating comprises a cold cranking ampere battery rating.
87. The apparatus of claim 81 including an input device wherein said computation circuitry computes state-of-health by comparing said total storage capacity with a reference number in accordance with a battery rating inputted on said input device.
88. The apparatus of claim 87 wherein said battery rating comprises an ampere-hour battery rating.
89. The apparatus of claim 87 wherein said battery rating comprises a reserve capacity battery rating.
90. Apparatus for determining a charge transfer conductance of an electrochemical cell or battery comprising:

10073376-020002

response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of time-varying electrical excitation of said cell or battery; and, computation circuitry coupled to said response sensing circuitry and adapted to utilize said response to evaluate elements of a circuit model containing a plurality of parallel G-C subcircuits connected in series, said computation circuitry further adapted to evaluate said charge transfer conductance from the value of the conductance element of a particular parallel G-C subcircuit.

91. Apparatus for determining a double layer capacitance of an electrochemical cell or battery comprising:
response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of time-varying electrical excitation of said cell or battery; and,
computation circuitry coupled to said response sensing circuitry and adapted to utilize said response to evaluate elements of a circuit model containing a

20250908-020802

plurality of parallel G-C subcircuits connected in series, said computation circuitry further adapted to evaluate said double layer capacitance from the value of the capacitance element of a particular parallel G-C subcircuit.

92. Apparatus for determining a maximum charge transfer conductance of an electrochemical cell or battery comprising:
- response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of time-varying electrical excitation of said cell or battery; and,
 - computation circuitry coupled to said response sensing circuitry and adapted to utilize said response to evaluate elements of a circuit model containing a plurality of parallel G-C subcircuits connected in series, said computation circuitry further adapted to evaluate said maximum charge transfer conductance from the values of the capacitance element of a particular parallel G-C subcircuit and the conductance element of a different parallel G-C subcircuit.

1007376-020003

93. Apparatus for determining a maximum double layer capacitance of an electrochemical cell or battery comprising:

response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of time-varying electrical excitation of said cell or battery; and,

computation circuitry coupled to said response sensing circuitry and adapted to utilize said response to evaluate elements of a circuit model containing a plurality of parallel G-C subcircuits connected in series, said computation circuitry further adapted to evaluate said maximum double layer capacitance from the values of the capacitance element of a particular parallel G-C subcircuit and the conductance element of a different parallel G-C subcircuit.

94. A method for determining the absolute stored charge of an electrochemical cell or battery comprising:

sensing time-varying electrical response to time-varying electrical excitation of said cell or battery;

10073378-020803

processing said time-varying electrical response to evaluate the capacitance element of a particular parallel G-C subcircuit of an electrical circuit representation of said cell or battery containing a plurality of said G-C subcircuits; and,

determining the value of said absolute stored charge from the value of said capacitance element.

95. A method for determining an exchange current of an electrochemical cell or battery comprising:

sensing time-varying electrical response to time-varying electrical excitation of said cell or battery; processing said time-varying electrical response to evaluate the conductance element of a particular parallel G-C subcircuit of an electrical circuit representation of said cell or battery; and,

determining the value of said exchange current from the value of said conductance element.

10073378-020803
20080308 09:40:01

96. A method for determining the state-of-charge of an electrochemical cell or battery comprising:

sensing time-varying electrical response to time-varying electrical excitation of said cell or battery; processing said time-varying electrical response to evaluate the capacitance element of a particular parallel G-C subcircuit and the conductance element of a different parallel G-C subcircuit of an electrical circuit representation of said cell or battery; and, determining the value of said state-of-charge from the value of said capacitance element and the value of said conductance element.

97. A method for determining the total storage capacity of an electrochemical cell or battery comprising:

sensing time-varying electrical response to time-varying electrical excitation of said cell or battery; processing said time-varying electrical response to evaluate the capacitance element of a particular parallel G-C subcircuit and the conductance element of a different

2000073378-020002

parallel G-C subcircuit of an electrical circuit representation of said cell or battery; and,
determining the value of said total storage capacity from the value of said capacitance element and the value of said conductance element.

98. A method for determining the maximum exchange current of an electrochemical cell or battery comprising:

sensing time-varying electrical response to time-varying electrical excitation of said cell or battery;
processing said time-varying electrical response to evaluate the capacitance element of a particular parallel G-C subcircuit and the conductance element of a different parallel G-C subcircuit of an electrical circuit representation of said cell or battery; and,
determining the value of said maximum exchange current from the value of said capacitance element and the value of said conductance element.

99. A method for determining the absolute cranking current of an electrochemical cell or battery comprising:

20250708-0200

sensing time-varying electrical response
to time-varying electrical
excitation of said cell or battery;
processing said time-varying electrical
response to evaluate the resistance
element of a series R-L subcircuit
of an electrical circuit
representation of said cell or
battery; and,
determining the value of said absolute
cranking current from the value of
said resistance element.

100. The method according to claim 99 further
applied to determining fully charged cranking
current including:

processing said time-varying electrical
response to evaluate the
capacitance element of a particular
parallel G-C subcircuit and the
conductance element of a different
parallel G-C subcircuit of said
electrical circuit representation
of said cell or battery; and,
correcting said absolute cranking
current with a correction factor
evaluated in accordance with values
of said capacitance element and
said conductance element to obtain

10073376-000000

said fully charged cranking
current.

101. The method of claim 100 further applied to determining state-of-health including:
inputting a battery rating; and,
comparing said fully charged cranking current with a reference number in accordance with said battery rating to determine said state-of-health.
102. The method of claim 101 wherein said battery rating is a cold cranking ampere battery rating.
103. The method of claim 97 further applied to determining state-of-health including:
inputting a battery rating; and,
comparing said total storage capacity with a reference number in accordance with said battery rating to determine said state-of-health.
104. The method of claim 103 wherein said battery rating is an ampere-hour battery rating.
105. The method of claim 103 wherein said battery rating is a reserve capacity battery rating.

10073378.020802

106. A method for determining a double layer capacitance of an electrochemical cell or battery comprising:

sensing time-varying electrical response
to time-varying electrical
excitation of said cell or battery;
processing said time-varying electrical
response to evaluate the
capacitance element of a particular
parallel G-C subcircuit of an
electrical circuit representation
of said cell or battery containing
a plurality of said G-C
subcircuits; and,
determining the value of said double
layer capacitance from the value of
said capacitance element.

107. A method for determining a charge transfer conductance of an electrochemical cell or battery comprising:

sensing time-varying electrical response
to time-varying electrical
excitation of said cell or battery;
processing said time-varying electrical
response to evaluate the
conductance element of a particular
parallel G-C subcircuit of an
electrical circuit representation
of said cell or battery; and,

10073378-020000

determining the value of said charge transfer conductance from the value of said conductance element.

108. A method for determining a maximum double layer capacitance of an electrochemical cell or battery comprising:

sensing time-varying electrical response to time-varying electrical excitation of said cell or battery; processing said time-varying electrical response to evaluate the capacitance element of a particular parallel G-C subcircuit and the conductance element of a different parallel G-C subcircuit of an electrical circuit representation of said cell or battery; and,

determining the value of said maximum double layer capacitance from the value of said capacitance element and the value of said conductance element.

109. A method for determining a maximum charge transfer conductance of an electrochemical cell or battery comprising:

sensing time-varying electrical response to time-varying electrical excitation of said cell or battery;

20073376-020007

processing said time-varying electrical response to evaluate the capacitance element of a particular parallel G-C subcircuit and the conductance element of a different parallel G-C subcircuit of an electrical circuit representation of said cell or battery; and, determining the value of said maximum charge transfer conductance from the value of said capacitance element and the value of said conductance element.

110. Apparatus for determining the absolute stored charge of an electrochemical cell or battery adapted to perform the method according to claim 94.
111. Apparatus for determining an exchange current of an electrochemical cell or battery adapted to perform the method according to claim 95.
112. Apparatus for determining state-of-charge of an electrochemical cell or battery adapted to perform the method according to claim 96.
113. Apparatus for determining the total storage capacity of an electrochemical cell or

10073376-020000

battery adapted to perform the method according to claim 97.

114. Apparatus for determining the maximum exchange current of an electrochemical cell or battery adapted to perform the method according to claim 98.
115. Apparatus for determining the absolute cranking current of an electrochemical cell or battery adapted to perform the method according to claim 99.
116. Apparatus for determining fully charged cranking current of an electrochemical cell or battery adapted to perform the method according to claim 100.
117. Apparatus for determining state-of-health of an electrochemical cell or battery adapted to perform the method according to claim 101.
118. Apparatus for determining state-of-health of an electrochemical cell or battery adapted to perform the method according to claim 103.
119. Apparatus for determining a double layer capacitance of an electrochemical cell or battery adapted to perform the method according to claim 106.

2007-03-26 10:00:00

determine said state-of-charge by combining values of said charge transfer conductance and said double layer capacitance.

124. A method for determining state-of-charge of an electrochemical cell or battery comprising:

sensing time-varying electrical response to time-varying electrical excitation of said cell or battery; processing said time-varying electrical response to evaluate a double layer capacitance and a charge transfer conductance; and, determining said state-of-charge by combining values of said double layer capacitance and said charge transfer conductance.

125. Apparatus for determining state-of-charge of an electrochemical cell or battery adapted to perform the method according to claim 124.

126. Apparatus for determining total storage capacity of an electrochemical cell or battery comprising:
response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said

10073376-00000000

cell or battery generated as a result of time-varying electrical excitation of said cell or battery; and, computation circuitry responsive to said time-varying response and adapted to evaluate a charge transfer conductance and a double layer capacitance, said computation circuitry further adapted to determine said total storage capacity by combining values of said charge transfer conductance and said double layer capacitance.

127. A method for determining total storage capacity of an electrochemical cell or battery comprising:

sensing time-varying electrical response to time-varying electrical excitation of said cell or battery; processing said time-varying electrical response to evaluate a double layer capacitance and a charge transfer conductance; and, determining said total storage capacity by combining values of said double layer capacitance and said charge transfer conductance.

128. Apparatus for determining total storage capacity of an electrochemical cell or

10073378-020808

battery adapted to perform the method according to claim 127.

129. Apparatus for determining absolute stored charge of an electrochemical cell or battery comprising:

response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of time-varying electrical excitation of said cell or battery; and,

computation circuitry responsive to said time-varying response and adapted to evaluate a double layer capacitance, said computation circuitry further adapted to determine said absolute stored charge from the value of said double layer capacitance.

130. A method for determining absolute stored charge of an electrochemical cell or battery comprising:

sensing time-varying electrical response to time-varying electrical excitation of said cell or battery; processing said time-varying electrical response to evaluate a double layer capacitance; and,

20250320 09:47:00

determining said absolute stored charge
from the value of said double layer
capacitance.

131. Apparatus for determining absolute stored
charge of an electrochemical cell or battery
adapted to perform the method according to
claim 130.

132. Apparatus for determining an exchange current
of an electrochemical cell or battery
comprising:

response sensing circuitry coupled to said
cell or battery and adapted to sense
time-varying electrical response of said
cell or battery generated as a result of
time-varying electrical excitation of
said cell or battery; and,

computation circuitry responsive to said
time-varying response and adapted to
evaluate a charge transfer conductance,
said computation circuitry further
adapted to determine said exchange
current from the value of said charge
transfer conductance.

133. A method for determining an exchange current
of an electrochemical cell or battery
comprising:

20073378-020002

sensing time-varying electrical response
to time-varying electrical
excitation of said cell or battery;
processing said time-varying electrical
response to evaluate a charge
transfer conductance; and,
determining said exchange current from
the value of said charge transfer
conductance.

134. Apparatus for determining an exchange current
of an electrochemical cell or battery adapted
to perform the method according to claim 133.
135. Apparatus for determining a maximum double
layer capacitance of an electrochemical cell
or battery comprising:
response sensing circuitry coupled to said
cell or battery and adapted to sense
time-varying electrical response of said
cell or battery generated as a result of
time-varying electrical excitation of
said cell or battery; and,
computation circuitry responsive to said
time-varying response and adapted to
evaluate a double layer capacitance and
a charge transfer conductance, said
computation circuitry further adapted to
determine said maximum double layer
capacitance from the values of said

20250902 09:00:00

double layer capacitance and said charge transfer conductance.

136. A method for determining a maximum double layer capacitance of an electrochemical cell or battery comprising:

sensing time-varying electrical response to time-varying electrical excitation of said cell or battery; processing said time-varying electrical response to evaluate a double layer capacitance and a charge transfer conductance; and, determining said maximum double layer capacitance from the values of said double layer capacitance and said charge transfer conductance.

137. Apparatus for determining a maximum double layer capacitance of an electrochemical cell or battery adapted to perform the method according to claim 136.

138. Apparatus for determining a maximum charge transfer conductance of an electrochemical cell or battery comprising:
response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of

10073378.020002

time-varying electrical excitation of said cell or battery; and, computation circuitry responsive to said time-varying response and adapted to evaluate a double layer capacitance and a charge transfer conductance, said computation circuitry further adapted to determine said maximum charge transfer conductance from the values of said double layer capacitance and said charge transfer conductance.

139. A method for determining a maximum charge transfer conductance of an electrochemical cell or battery comprising:
- sensing time-varying electrical response to time-varying electrical excitation of said cell or battery;
 - processing said time-varying electrical response to evaluate a double layer capacitance and a charge transfer conductance; and,
 - determining said maximum charge transfer conductance from the values of said double layer capacitance and said charge transfer conductance.
140. Apparatus for determining a maximum charge transfer conductance of an electrochemical

1007376-0000

cell or battery adapted to perform the method according to claim 139.

141. Apparatus for determining a maximum exchange current of an electrochemical cell or battery comprising:

response sensing circuitry coupled to said cell or battery and adapted to sense time-varying electrical response of said cell or battery generated as a result of time-varying electrical excitation of said cell or battery; and,

computation circuitry responsive to said time-varying response and adapted to evaluate a double layer capacitance and a charge transfer conductance, said computation circuitry further adapted to determine said maximum exchange current from the values of said double layer capacitance and said charge transfer conductance.

142. A method for determining a maximum exchange current of an electrochemical cell or battery comprising:

sensing time-varying electrical response to time-varying electrical excitation of said cell or battery; processing said time-varying electrical response to evaluate a double layer

1007378-020004

capacitance and a charge transfer conductance; and,
determining said maximum exchange current from the values of said double layer capacitance and said charge transfer conductance.

143. Apparatus for determining a maximum exchange current of an electrochemical cell or battery adapted to perform the method according to claim 142.

20250927 09:00:00